Product data sheet Characteristics

ZA2BD5

selector switch head - 3 positions Ø 22 - black

Product availability: Stock - Normally stocked in distribution facility

Price*: 36.80 USD



Main

Range of product	Harmony XAC	
Product or component type	Selector switch	
Component name	ZA2	
Product compatibility	XACA	

Complementary

Marking	Unmarked	
Cap/Operator or lens colour	Black	
Sale per indivisible quantity	1	
Product weight	0.04 lb(US) (0.018 kg)	

Environment

Main		
Range of product	Harmony XAC	
Product or component type	Selector switch	
Component name	ZA2	
Product compatibility	XACA	
Complementary		
Marking	Unmarked	
Cap/Operator or lens colour	Black	
Sale per indivisible quantity	1	
Product weight	0.04 lb(US) (0.018 kg)	
	LII 508	
Environment Standards	UL 508 EN/IEC 60204-32	
	EN/IEC 60204-32 CSA C22.2 No 14	
Standards	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1	
Standards Ambient air temperature for operation	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C)	
Standards Ambient air temperature for operation Ambient air temperature for storage	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C)	
Standards Ambient air temperature for operation Ambient air temperature for storage Vibration resistance	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6	
Ambient air temperature for operation Ambient air temperature for storage Vibration resistance Shock resistance	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6 100 gn conforming to IEC 60068-2-27	
Ambient air temperature for operation Ambient air temperature for storage Vibration resistance Shock resistance Overvoltage category	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6 100 gn conforming to IEC 60068-2-27 Class II conforming to IEC 61140	
Ambient air temperature for operation Ambient air temperature for storage Vibration resistance Shock resistance Overvoltage category IP degree of protection	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6 100 gn conforming to IEC 60068-2-27 Class II conforming to IEC 61140 IP65 conforming to IEC 60529	
Ambient air temperature for operation Ambient air temperature for storage Vibration resistance Shock resistance Overvoltage category IP degree of protection	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6 100 gn conforming to IEC 60068-2-27 Class II conforming to IEC 61140	
Standards Ambient air temperature for operation	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6 100 gn conforming to IEC 60068-2-27 Class II conforming to IEC 61140 IP65 conforming to IEC 60529	
Ambient air temperature for operation Ambient air temperature for storage Vibration resistance Shock resistance Overvoltage category IP degree of protection	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6 100 gn conforming to IEC 60068-2-27 Class II conforming to IEC 61140 IP65 conforming to IEC 60529	
Ambient air temperature for operation Ambient air temperature for storage Vibration resistance Shock resistance Overvoltage category IP degree of protection IK degree of protection	EN/IEC 60204-32 CSA C22.2 No 14 EN/IEC 60947-5-1 -13158 °F (-2570 °C) -40158 °F (-4070 °C) 15 gn (f = 10500 Hz) conforming to IEC 60068-2-6 100 gn conforming to IEC 60068-2-27 Class II conforming to IEC 61140 IP65 conforming to IEC 60529	

Ordering and shipping details

Category	22460 - PUSHBUTTONS 22MM (PLASTIC)
Discount Schedule	CS2

GTIN	00785901648567
Nbr. of units in pkg.	1
Package weight(Lbs)	4.0000000000001E-2
Returnability	N
Country of origin	FR

Contractual warranty

Warranty period	18 months