Product data sheet Characteristics

ZB4BW333 green flush illuminated pushbutton head Ø22 spring return for integral LED

Product availability : Stock - Normally stocked in distribution facility



Main

Main		
Range of product	Harmony XB4	
Product or component type	Head for illuminated push-button	
Device short name	ZB4	
Product compatibility	Integral LED	
Bezel material	Chromium plated metal	
Mounting diameter	0.87 in (22 mm)	
Sale per indivisible quantity	1	
Shape of signaling unit head	Round	
Type of operator	Spring return	
Operator profile	Green flush unmarked	
Operator additional information		
Operator additional information	With plain lens	
	with plain tens	
	with plain tens	
Complementary	•	
Complementary CAD overall width	1.14 in (29 mm)	
Complementary CAD overall width CAD overall height	1.14 in (29 mm) 1.14 in (29 mm)	
Complementary CAD overall width CAD overall height CAD overall depth	1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm)	
Complementary CAD overall width CAD overall height CAD overall depth Product weight	1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg)	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer	1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer Mechanical durability	1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer Mechanical durability	1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles M1 <= 6 contacts using single blocks in front mounting with integral LED	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer Mechanical durability	1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer Mechanical durability	1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles M1 <= 6 contacts using single blocks in front mounting with integral LED	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer	1.14 in (29 mm) 1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles M1 <= 6 contacts using single blocks in front mounting with integral LED	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer Mechanical durability Electrical composition code	1.14 in (29 mm) 1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles M1 <= 6 contacts using single blocks in front mounting with integral LED	
Complementary CAD overall width CAD overall height CAD overall depth Product weight Resistance to high pressure washer Mechanical durability	1.14 in (29 mm) 1.14 in (29 mm) 1.14 in (29 mm) 1.18 in (30 mm) 0.06 lb(US) (0.026 kg) 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m 10000000 cycles M1 <= 6 contacts using single blocks in front mounting with integral LED	

Complementary

1.14 in (29 mm)
1.14 in (29 mm)
1.18 in (30 mm)
0.06 lb(US) (0.026 kg)
1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m
1000000 cycles
M1 <= 6 contacts using single blocks in front mounting with integral LED M2 <= 6 contacts using single and double blocks in front mounting with integral LED M10 <= 2 contacts using single blocks in front mounting with integral LED M6 <= 2 contacts using single blocks in front mounting with integral LED and transformer

Environment

Protective treatment	TH
Ambient air temperature for storage	-40158 °F (-4070 °C)

Life Is On Schneider

Ambient air temperature for operation	-40158 °F (-4070 °C)
Overvoltage category	Class I conforming to IEC 60536
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK06 conforming to EN 50102
Standards	CSA C22.2 No 14 UL 508 EN/IEC 60947-5-4 EN/IEC 60947-5-1 JIS C 4520 EN/IEC 60947-5-5 EN/IEC 60947-1
Product certifications	BV CSA GL UL listed DNV RINA LROS (Lloyds register of shipping)
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	00785901353829
Nbr. of units in pkg.	1
Package weight(Lbs)	5.999999999999998E-2
Returnability	Y
Country of origin	FR

Contractual warranty

Warranty period

18 months