



Actual



Representative

Catalog Number: 2234
Product ID: 7TBD105140R0003
UPC Number: 78621002234
Status: Active

Watertight Connector for Oval Cable, Hub Size 3/4 Inch, Die Cast Zinc Body with Neoprene Bushing, Oval Cable Range Maximum .555 X .800 Inch, Minimum .490 X .675 Inch

- The tapered neoprene bushings are resistant to oil, sunlight and water. Hex gland and body take the same wrench opening and a stainless steel slip ring prevents cable from twisting as gland ring is being tightened. Threads on the body are tapered for water

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Type	Watertight Connectors for Oval Cable
Special Features	A Design with Two Tapers Inside the Body-A Slow One and a Fast One-Permits the Stocking of Fewer Connectors for Varied Cable Sizes and Allows Maximum Take-Up.
Application	To Connect Underground Feeder Cables to a Box or an Enclosure
Standard	UL E15170, CSA 4484
Size	3/4 Inch
Conductor Range	.490x.675 to .555x.800 Inch
Material	Zinc Die Cast
Color	Metallic

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	3/4 inch
Material	Metal
Material quality	Other
Colour	Natural colour
Model	Straight

Packaging

Inner Quantity	10
Inner Dimensions (inches)	4x4x3
Outer Quantity	100
Outer Dimensions (inches)	21.5x8.5x3.5
Weight Uom	5.88 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com