


## 4 and 5-Pin Field Wireable Connectors, Standard with Labels

- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>B 81..</b></p>	<p><b>B 8141-0/LABEL</b> <b>B 8241-0/LABEL</b></p>	<p><b>BS 8141-0/LABEL</b> <b>BS 8241-0/LABEL</b></p>	<p>PBT, Black, PG 7 cable gland accepts 4-6 mm cable diameter, screw terminals accepts up to 18 AWG conductors, 85°C, 250 V, 4 A, mates with standard key 4-pin cordsets and receptacles, color coded &amp; numbered pins</p>	<p><b>Female</b></p>
<p><b>B 82..</b></p>	<p><b>B 8141-0/PG9/LABEL</b> <b>B 8241-0/PG9/LABEL</b></p>	<p><b>BS 8141-0/PG9/LABEL</b> <b>BS 8241-0/PG9/LABEL</b></p>	<p>PBT, Black, PG 9 cable gland accepts 6-8 mm cable diameter, screw terminals, 85°C, 250 V, 4 A, mates with standard key 4-pin cordsets and receptacles, color coded &amp; numbered pins</p>	<p><b>Male</b></p>
<p><b>BS 81..</b></p>	<p><b>B 8151-0/PG9/LABEL</b> <b>B 8251-0/PG9/LABEL</b></p>	<p><b>BS 8151-0/PG9/LABEL</b> <b>BS 8251-0/PG9/LABEL</b></p>	<p>PBT, Black, PG 9 cable gland accepts 4-8 mm cable diameter, screw terminals accepts up to 18 AWG conductors, 85°C, 60 V, 4 A, mates with standard key 5-pin cordsets and receptacles, color coded &amp; numbered pins</p>	<p><b>Female</b></p>
<p><b>BS 82..</b></p>	<p><b>B 8151-0/PG9/LABEL</b> <b>B 8251-0/PG9/LABEL</b></p>	<p><b>BS 8151-0/PG9/LABEL</b> <b>BS 8251-0/PG9/LABEL</b></p>	<p>PBT, Black, PG 9 cable gland accepts 4-8 mm cable diameter, screw terminals accepts up to 18 AWG conductors, 85°C, 60 V, 4 A, mates with standard key 5-pin cordsets and receptacles, color coded &amp; numbered pins</p>	<p><b>Male</b></p>

Field Wireables