


WAC LIGHTING

Responsible Lighting®







Actual Size

Power: 3W / ft
Lumens: Up to 215 lm / ft
CRI: 85
Rated Life: 50,000 hours

- Designed for bright cove or task lighting
- UL listed for damp location
- 5 year warranty

- Maximum run length of 33 feet
- May be field cut every 2 inches at the end of a run
- Smooth and continuous ELV dimming



Tape Selections

System	Color Temp	Length	Qty	Finish
LED-T24	W 2700K	2IN 2 inches	1	WT White
	P 3000K	2IN-10 2 inches	10	
	35 3500K	1 1 foot	1	
	C 4500K	5 5 feet	1	
		1-40 1 foot	40	

Example: **LED-T24W-1-40-WT**

"L" Connector

System	Color Temp	Finish
LED-T24	W 2700K	3L-WT White
	P 3000K	
	35 3500K	
	C 4500K	

Example: **LED-T24W-3L-WT**

Each "L" connector consumes 1.2 watt

Class 2 Power Supply for Pro (Required)














Type	Model	Power	Dim	Input	Output
Remote	EN-2460-RB2-T	60W	Yes	120V AC	24V AC
	EN-24100-RB2-T	96W	Yes	120V AC	24V AC
Plug-in	EN-2460-P-AR-T	60W	Yes	120V AC	24V AC
	EN-24100-P-AR-T	96W	Yes	120V AC	24V AC
Remote 277V	EN-24100-277-R	96W	No	277V AC	24V DC

Includes a 6 foot lead wire

Includes a 6 foot lead wire

Order with LED-TC-B-2 or LED-T-EXT-144

Accessories

Rigid Aluminum Channel		LED-T-CH	5 ft	Includes mounting hardware and diffuser lens Field cuttable
Lead Wire		LED-TC-P-2 LED-TC-P-12	2 ft 12 ft	Alternative lengths for plug-in power supplies
Extension Cable		LED-TC-EXT-144	12 ft	Extends distance between a hard wired power supply or wiring box to a tape section
Low Voltage Wiring Box With Feed		LED-TC-B-2	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly houses up to two wires with 2" female feed
Low Voltage Wiring Box		LED-T-B	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly houses up to two wires
Wiring Box With Switch		TB-S	L: 6 1/4 in W: 1 3/8 in H: 1 1/4 in	Use when spanning a large gap in a system layout without leaving exposed wiring
Joiner Cable		LED-TC-IC2 LED-TC-IC6 LED-TC-IC12 LED-TC-IC36 LED-TC-IC72	2 in 6 in 12 in 36 in 72 in	Use between tape sections
"L" Connector		LED-TC-L		
3-Way "Y" Connector		LED-TC-Y		
4-Way "X" Connector		LED-TC-X		
End cap		LED-TC-EC		1 cut end cap 1 male end cap
Mounting Clips		LED-T-CL	10 Qty	
Retrofit Channel		LED-T-RC	36 in	