Disc

LED Ceiling and Wall

WAC LIGHTING

Responsible Lighting®



Fixture Type:	
Catalog Number	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Multiple mid-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows which are common in conventional flush mounts.

FEATURES

- Install over a junction box or retrofit over a 5" or 6" recessed can
- Energy Star® rated
- Wet Location Listed
- CEC Title 24 Compliant
- CSA listed
- ADA compliant
- Wall or Ceiling Mount
- Opaque acrylic diffuser
- Multiple LED array for uniform illumination
- 120VAC no driver needed
- $\bullet \ \mathsf{Smooth} \ \mathsf{and} \ \mathsf{continuous} \ \mathsf{ELV} \ \mathsf{dimming}$
- Rated Life: 50,000 hours

SPECIFICATIONS

Construction: Steel with white acrylic diffuser

Input: 120VAC

ELV Dimming: 100% - 10% Electronic Low Voltage

Harmonic Distortion (THD): 16% for Input Current at 120VAC

Operating Temperature Range: -40°C to 85°C

ORDERING NUMBER

		Watt	Color ⁻	Гетр	CRI	LED Lumens	Delivered Lumens	Finisl	n	
7%" I 1¼"	FM-306	15W	930	3000K	90	1110	865	BN BZ WT	Brushed nickel Bronze White	

FM - 306 - 930 -	
------------------	--

Example: FM-306-930-WT

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585