
HR-LED87

LEDme® Button Light

WAC LIGHTING

Responsible Lighting®








Recessed Mount

17%'



Catalog Number:

Project:

Location:





-2¼"

PRODUCT DESCRIPTION

Designed for recessed or surface mounted installations, delivering strong light output with the latest in LED technology.

FEATURES

- · Recessed or surface mounting
- · Quick and easy installation
- Includes 72" lead wire
- 3000K color temperature
- 70,000 hour rated life
- UI and CUI Listed
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

	Watt	Lumens	Efficacy	CRI
HR-LED87	5W	180	36 Lm/W	85
HR-LED87S	4.8W	155	32.3 Lm/W	

SPECIFICATIONS

Construction: Die-cast aluminum fixture, stamped steel housing for surface mount. Glass beam spread lens.

Wiring: Includes 72" pre-installed wires that lead out through the top.

Transformers: Class 2, 24V remote and plug-in transformers allow for up to 20 button lights to be wired together. Use a multiple terminal block to wire up to 6 fixtures in a neat under cabinet installation without the use of open splices (see below).

Light Source: Six 3000K LEDs.

Dimming: May be dimmed to 10% with an electronic low voltage (ELV) dimmer.

Mounting: Recessed - 21/8" cutout hole. Compression springs hold fixture firmly in place. Surface - Screw housing cover to surface, compress springs and insert into cover. Not recommended for use in ceiling.

Finish: Black (BK), Dark Bronze (DB) and White (WT) powder coat, electroplated Brushed Nickel (BN), Copper Bronze (CB) and Chrome (CH).

Standards: UL & CUL Listed.


ORDER NUMBER

Model #		Color Temp	Finish	1
HR-LED87 HR-LED87S	Round Square	3000K	BK BN CB	Black Brushed Nickel Copper Bronze
HR-LED87-27 HR-LED87S-27	Round Square	2700K	CH DB WT	Chrome Dark Bronze White



Example: HR-LED87S-27-BN

- · Minimizes wiring back to transformer
- No voltage drop, power supplied using a variable current
- · If one fixture goes out the rest remain on



FINISHES











RETROFIT RECESSED HOUSING

I	HR-LED-COV	BK, BN, CB, CH, DB, WT
ı	Model #	Finish

Use to replace low voltage HR-88 and HR-86 button lights using existing wiring and cutout.

CLASS 2 ELECTRONIC TRANSFORMERS

Туре	Model	Dim	Input	Output	Power Up To	Dimensions
Domoto	EN-2460-RB2	Yes	120V	24V AC/60W	12 × LED87	6½"×15/8"×11/4"
Remote	EN-24100-RB2			24V AC/96W	20 × LED87	6½"×15%"×1¼"
Plug-In	EN-2460-P-AR	Yes	120V	24V AC/60W	12 × LED87	2¾" X 1½" X 1¾"

Includes 6' cord and 5 SL-WC-1 clips.

MULTIPLE TERMINAL BLOCK

Model #	Dimensions				
MTB-01	L: 3¼"	W: 1¾"	H: %"		

12.5A max accommodates up to 6 output connections for 14 AWG wires.

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 615 South Street • Garden City, NY 11530 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

168 Brea Canyon Road • City of Industry, CA 91789 Phone (800) 526.2588 • Fax (800) 526.2585