


# WAC LIGHTING

Responsible Lighting®







**Power:** 3W/ft  
**Lumens:** Up to 215 lm/ft  
**CRI:** 85  
**Rated Life:** 50,000 hours

- Designed for bright cove or task lighting
- UL listed for damp location
- 5 year warranty

- Maximum run length of 33 feet
- May be field cut every 2 inches at the end of a run
- Smooth and continuous ELV dimming



## Tape Selections

System	Color Temp	Length	Qty	Finish
<b>LED-T24</b>	<b>W</b> 2700K	<b>2IN</b> 2 inches	1	<b>WT</b> White
	<b>P</b> 3000K	<b>2IN-10</b> 2 inches	10	
	<b>35</b> 3500K	<b>1</b> 1 foot	1	
	<b>5</b> 5 feet		1	
	<b>C</b> 4500K	<b>1-40</b> 1 foot	40	

Example: **LED-T24W-1-40-WT**

## "L" Connector

System	Color Temp	Finish
<b>LED-T24</b>	<b>W</b> 2700K	<b>3L-WT</b> White
	<b>P</b> 3000K	
	<b>35</b> 3500K	
	<b>C</b> 4500K	

Example: **LED-T24W-3L-WT**

Each "L" connector consumes 1.2 watt

## Class 2 Power Supply for Pro (Required)

Type	Model	Power	Dim	Input	Output
Remote	<b>EN-2460-RB2-T</b>	60W	Yes	120V AC	24V AC
	<b>EN-24100-RB2-T</b>	96W			24V AC
Plug-in	<b>EN-2460-P-AR-T</b>	60W	Yes	120V AC	24V AC
	<b>EN-24100-P-AR-T</b>	96W			24V AC
Remote 277V	<b>EN-24100-277-R</b>	96W	No	277V AC	24V DC

*Includes a 6 foot lead wire*

*Includes a 6 foot lead wire*

*Order with LED-TC-B-2 or LED-T-EXT-144*

## Accessories

Rigid Aluminum Channel		<b>LED-T-CH</b>	5 ft	Includes mounting hardware and diffuser lens Field cuttable
Lead Wire		<b>LED-TC-P-2</b> <b>LED-TC-P-12</b>	2 ft 12 ft	Alternative lengths for plug-in power supplies
Extension Cable		<b>LED-TC-EXT-144</b>	12 ft	Extends distance between a hard wired power supply or wiring box to a tape section
Low Voltage Wiring Box With Feed		<b>LED-TC-B-2</b>	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly houses up to two wires with 2" female feed
Low Voltage Wiring Box		<b>LED-T-B</b>	L: 1 1/2 in W: 3/4 in H: 7/8 in	Neatly houses up to two wires
Wiring Box With Switch		<b>TB-S</b>	L: 6 1/4 in W: 1 3/8 in H: 1 1/4 in	Use when spanning a large gap in a system layout without leaving exposed wiring
Joiner Cable		<b>LED-TC-IC2</b> <b>LED-TC-IC6</b> <b>LED-TC-IC12</b> <b>LED-TC-IC36</b> <b>LED-TC-IC72</b>	2 in 6 in 12 in 36 in 72 in	Use between tape sections
"L" Connector		<b>LED-TC-L</b>		
3-Way "Y" Connector		<b>LED-TC-Y</b>		
4-Way "X" Connector		<b>LED-TC-X</b>		
End cap		<b>LED-TC-EC</b>		1 cut end cap 1 male end cap
Mounting Clips		<b>LED-T-CL</b>	10 Qty	
Retrofit Channel		<b>LED-T-RC</b>	36 in	