


Ground Rod Clamp, Rod to Conductor, Bronze – CP34



- For use with copper-bonded ground rods
- Parts that are UL Listed are suitable for direct burial in earth or concrete



Part Number	CP34
Torque [TQ]	150 – 300 in lb
Material	Silicon Bronze
Ground Rod Diameter, Nominal	1/2" – 3/4"
Ground Rod Diameter, Actual (Ø)	0.50" – 0.68"
Conductor Size	#10 Solid - 1/0 Stranded 6 mm ² Solid - 50 mm ² Stranded
Wrench Size	1/2"
Certifications	CSA 46866 cULus
Standard Packaging Quantity	50 pc
UPC	78285630704
EAN-13	8711893041682

CSA, CSA-US and C-CSA-US are registered trademarks of Canadian Standards Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.